

List No. SB619

APPLEBY SERVICE ITEMS

1 Gang Dry Lining Installation Box with Adjustable Lugs 35mm



- Made from flame retardant thermoplastic
- Tough yellow nylon lugs have large bearing faces for superior strength
- Large flange around the front matches profile of accessory front plates and prevents slipping into the cavity
- 25mm base knockout plus 2 side cable entry points.
- Appropriate for fitting board thicknesses from 6.35-15mm

Product Specification Data

Revision Date: 25/02/2025

CE Conformity	Yes
UKCA Conformity	Yes
Mounting method	Flush-mounted
Shape	Square
Construction type	Device connection box (round/square)
Model	Single
Length	83 mm
Width	83 mm
Depth	36 mm
Inner depth	35 mm
For number of electric fittings	1
Mounting switching equipment	Screwing
With screws	No
Material	Plastic
Halogen free	Yes
Surface protection	Untreated
Colour	White
Degree of protection (IP)	Other
Cover model	Other
Cover attachment	Screwed

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



Unelex Limited
Suite 117B, Building A, 25 Goodlass Road, Speke, Liverpool
Tel: 0151 665 0860 **Email:** sales@appleby-sales.co.uk